

2N7002K-AU

60V N-Channel Enhancement Mode MOSFET – ESD Protected


Voltage **60 V** **Current** **300mA**

Features

- $R_{DS(ON)}$, $V_{GS} @ 10V$, $I_D @ 500mA < 3\Omega$
- $R_{DS(ON)}$, $V_{GS} @ 4.5V$, $I_D @ 200mA < 4\Omega$
- Advanced Trench Process Technology
- High Density Cell Design For Ultra Low On-Resistance
- Very Low Leakage Current In Off Condition
- Specially Designed for Battery Operated Systems, Solid-State Relays Drivers: Relay, Displays, Memories, etc
- ESD Protected 2kV HBM
- AEC-Q101 qualified
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case: SOT-23 Package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0003 ounces, 0.0084 grams



Maximum Ratings and Thermal Characteristics ($T_A=25^\circ C$ unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNITS
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	± 20	
Continuous Drain Current (Note 4)	I_D	300	mA
Pulsed Drain Current (Note 1)	I_{DM}	2000	
Power Dissipation	P_D	500	mW
		4	$mW/^\circ C$
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55~150	$^\circ C$
Typical Thermal Resistance - Junction to Ambient (Note 3,4)	$R_{\theta JA}$	250	$^\circ C/W$

2N7002K-AU

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)







PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_{\text{D}}=10\text{\mu A}$	60	-	-	V
Gate Threshold Voltage	$\text{V}_{\text{GS}(\text{th})}$	$\text{V}_{\text{DS}}=\text{V}_{\text{GS}}, \text{I}_{\text{D}}=250\text{\mu A}$	1	-	2.5	
Drain-Source On-State Resistance	$\text{R}_{\text{DS}(\text{on})}$	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_{\text{D}}=500\text{mA}$	-	-	3	Ω
		$\text{V}_{\text{GS}}=4.5\text{V}, \text{I}_{\text{D}}=200\text{mA}$	-	-	4	
Zero Gate Voltage Drain Current	I_{DSS}	$\text{V}_{\text{DS}}=60\text{V}, \text{V}_{\text{GS}}=0\text{V}$	-	-	1	\mu A
Gate-Source Leakage Current	I_{GSS}	$\text{V}_{\text{GS}}=\pm 20\text{V}, \text{V}_{\text{DS}}=0\text{V}$	-	-	± 10	
Forward Transconductance	g_{fs}	$\text{V}_{\text{DS}}=15\text{V}, \text{I}_{\text{D}}=250\text{mA}$	100	-	-	mS
Dynamic (Note 5)						
Total Gate Charge	Q_{g}	$\text{V}_{\text{DS}}=15\text{V}, \text{I}_{\text{D}}=250\text{mA}, \text{V}_{\text{GS}}=5\text{V}$ (Note 1,2)	-	0.8	-	nC
Gate-Source Charge	Q_{gs}		-	0.35	-	
Gate-Drain Charge	Q_{gd}		-	0.2	-	
Input Capacitance	C_{iss}	$\text{V}_{\text{DS}}=25\text{V}, \text{V}_{\text{GS}}=0\text{V}, f=1\text{MHZ}$	-	35	-	pF
Output Capacitance	C_{oss}		-	13	-	
Reverse Transfer Capacitance	Crss		-	8	-	
Turn-On Delay Time	$\text{t}_{\text{d}(\text{on})}$	$\text{V}_{\text{DD}}=30\text{V}, \text{I}_{\text{D}}=200\text{mA}, \text{V}_{\text{GS}}=10\text{V}, \text{R}_{\text{G}}=10\Omega$ (Note 1,2)	-	2.7	-	ns
Turn-On Rise Time	tr		-	19	-	
Turn-Off Delay Time	$\text{t}_{\text{d}(\text{off})}$		-	15	-	
Turn-Off Fall Time	tf		-	23	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I_{s}	---	-	-	300	mA
Diode Forward Voltage	V_{SD}	$\text{I}_{\text{s}}=200\text{mA}, \text{V}_{\text{GS}}=0\text{V}$	-	0.82	1.3	V

NOTES:

1. Pulse width $\leq 300\text{\mu s}$, Duty cycle $\leq 2\%$.
2. Essentially independent of operating temperature typical characteristics.
3. R_{QJA} is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins mounted on a 1 inch FR-4 with 2oz. square pad of copper.
4. The maximum current rating is package limited.
5. Guaranteed by design, not subject to production testing.





2N7002K-AU

TYPICAL CHARACTERISTIC CURVES



2N7002K-AU

TYPICAL CHARACTERISTIC CURVES




2N7002K-AU

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
2N7002K-AU	SOT-23	3K pcs / 7" reel	K72

Mounting Pad Layout



2N7002K-AU

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.