

MMBT2369A

NPN GENERAL PURPOSE SWITCHING TRANSISTOR

VOLTAGE 15 Volts **POWER** 225 mWatts

FEATURES

- NPN epitaxial silicon, planar design
- Collector-emitter voltage $V_{CE} = 15V$
- Collector current $I_C = 200mA$
- Lead free in comply with EU RoHS 2011/65/EU directives.
- Green molding compound as per IEC61249 Std. . (Halogen Free)

MECHANICAL DATA

- Case: SOT-23, Plastic
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0084 grams
- Marking: M3B





Fig.34

SOT-23 Unit: inch (mm)



ABSOLUTE RATINGS

PARAMETER	Symbol	Value	Units
Collector - Emitter Voltage	V_{CEO}	15	V
Collector - Base Voltage	V_{CBO}	40	V
Emitter - Base Voltage	V_{EBO}	4.5	V
Collector Current - Continuous	I_C	200	mA

THERMAL CHARACTERISTICS

PARAMETER	Symbol	Value	Units
Max Power Dissipation (Note 1)	P_{TOT}	225	mW
Thermal Resistance , Junction to Ambient	$R_{\theta JA}$	556	$^{\circ}C/W$
Junction Temperature	T_J	-55 to 150	$^{\circ}C$
Storage Temperature	T_{STG}	-55 to 150	$^{\circ}C$

Note 1: Transistor mounted on FR-4 board 70 x 60 x 1mm.

MMBT2369A





ELECTRICAL CHARACTERISTICS

PARAMETER	Symbol	Test Condition	MIN.	MAX.	Units
OFF CHARACTERISTICS					
Collector - Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C=10mA, I_B=0$	15	-	V
Collector - Emitter Breakdown Voltage	$V_{(BR)CES}$	$I_C=10\mu A, I_B=0$	40	-	V
Collector - Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C=10\mu A, I_E=0$	40	-	V
Emitter - Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E=10\mu A, I_C=0$	4.5	-	V
Collector Cutoff Current	I_{CBO}	$V_{CB}=20V, I_E=0$ $V_{CB}=20V, I_E=0, T_A=125^\circ C$		0.4 30	μA μA
ON CHARACTERISTICS					
DC Current Gain (Note 2)	h_{FE}	$I_C=10mA, V_{CE}=1.0V$ $I_C=10mA, V_{CE}=0.35V, T_A=-55^\circ C$ $I_C=30mA, V_{CE}=0.4V$ $I_C=100mA, V_{CE}=1.0V$	40 40 30 20	120	-
Collector - Emitter Saturation Voltage (Note 2)	$V_{CE(SAT)}$	$I_C=10mA, I_B=1.0mA$ $I_C=10mA, I_B=1.0mA, T_A=125^\circ C$ $I_C=30mA, I_B=3.0mA$ $I_C=100mA, I_B=10mA$	-	0.2 0.3 0.25 0.5	V
Base - Emitter Saturation Voltage (Note 2)	$V_{BE(SAT)}$	$I_C=10mA, I_B=1.0mA$ $I_C=10mA, I_B=1.0mA, T_A=-55^\circ C$ $I_C=10mA, I_B=1.0mA, T_A=125^\circ C$ $I_C=30mA, I_B=3.0mA$ $I_C=100mA, I_B=10mA$	0.7 0.59	0.85 1.02 1.15 1.6	V
SMALL SIGNAL CHARACTERISTICS					
Output Capacitance	C_{OBO}	$V_{CB}=5V, I_E=0, f=1MHz$	-	4.0	pF
Input Capacitance	C_{IBO}	$V_{CB}=0.5V, I_C=0, f=1MHz$	-	5.0	pF
Small-Signal Current Gain	h_{FE}	$I_C=10mA, V_{CE}=10V,$ $R_G=2.0k\Omega, f=100MHz$	5.0	-	-
SWITCHING CHARACTERISTICS					
Storage Time	t_s	$I_B1=I_B2=I_C=10mA$	-	13	ns
Turn-On Time	t_{on}	$V_{CC}=3V, I_C=10mA$ $I_B1=3.0mA$	-	12	ns
Turn-Off Time	t_{off}	$V_{CC}=3V, I_C=10mA$ $I_B1=3.0mA, I_B2=1.5mA$	-	18	ns

Note 2: Pulse Test: Pulse Width $\leq 300 \mu s$, Duty Cycle $\leq 2.0\%$.


MMBT2369A

ELECTRICAL CHARACTERISTICS CURVE



MMBT2369A

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
 - T/R - 12K per 13" plastic Reel
 - T/R - 3K per 7" plastic Reel

MMBT2369A

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.