
PEC4102AS ~ PEC4105AS Series

ESD Protection

Voltage **2.5~5 V**

SOD-123





Features

- IEC61000-4-2(ESD) : ± 15 kV Air, ± 8 kV Contact Compliance with the capability up to ± 30 kV
- IEC61000-4-5(Lightning) : 20~30A(8/20uS)
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : SOD-123 Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.0104 grams

Maximum Ratings and Thermal Characteristics (T_A = 25 °C unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNITS
ESD IEC61000-4-2(Air) ESD IEC61000-4-2(Contact)	V_{ESD}	±30 ±30	kV
Typical Thermal Resistance(Note 1)	$R_{\theta JA}$	510	°C/W
Operating Junction Temperature Range	T_J	-55~150	°C
Storage Temperature Range	T_{STG}	-55~150	°C

PEC4102AS ~ PEC4105AS Series

Electrical Characteristics (T_A = 25 °C unless otherwise noted)

PEC4102AS						
PARAMETER	**SYMBOL**	**TEST CONDITION**	**MIN.**	**TYP.**	**MAX.**	**UNITS**
Reverse Stand-Off Voltage(Note 2)	V_{RWM}	-	-	-	2.5	V
Reverse Breakdown Voltage	V_{BR}	I_{BR} = 50 mA	2.6	-	4	V
Reverse Leakage Current	I_R	V_R = 2.5 V	-	-	0.5	uA
Clamping Voltage	V_{CL}	I_{PP} = 1 A, t_P = 8/20 us	-	-	4.5	V
		I_{PP} = 30 A, t_P = 8/20 us	-	-	9	
Off State Junction Capacitance	C_J	0Vdc Bias f = 1 MHz	-	-	120	pF

PEC4103AS						
PARAMETER	**SYMBOL**	**TEST CONDITION**	**MIN.**	**TYP.**	**MAX.**	**UNITS**
Reverse Stand-Off Voltage(Note 2)	V_{RWM}	-	-	-	3.3	V
Reverse Breakdown Voltage	V_{BR}	I_{BR} = 50 mA	3.5	-	4.5	V
Reverse Leakage Current	I_R	V_R = 3.3 V	-	-	0.5	uA
Clamping Voltage	V_{CL}	I_{PP} = 1 A, t_P = 8/20 us	-	-	5.5	V
		I_{PP} = 30 A, t_P = 8/20 us	-	-	9	
Off State Junction Capacitance	C_J	0Vdc Bias f = 1 MHz	-	-	100	pF

PEC4105AS						
PARAMETER	**SYMBOL**	**TEST CONDITION**	**MIN.**	**TYP.**	**MAX.**	**UNITS**
Reverse Stand-Off Voltage(Note 2)	V_{RWM}	-	-	-	5	V
Reverse Breakdown Voltage	V_{BR}	I_{SB} = 50 mA	5.5	-	8	V
Reverse Leakage Current	I_R	V_R = 5 V	-	-	0.5	uA
Clamping Voltage	V_{CL}	I_{PP} = 1 A, t_P = 8/20 us	-	-	10	V
		I_{PP} = 20 A, t_P = 8/20 us	-	-	13	
Off State Junction Capacitance	C_J	0Vdc Bias f = 1 MHz	-	-	80	pF

NOTES :

1. Mounted on a FR4 PCB, single-sided copper, standard footprint.
2. A transient suppressor is selected according to the working peak reverse voltage(V_{RWM}), which should be equal to or greater than the DC or continuous peak operation voltage level.

PEC4102AS ~ PEC4105AS Series

TYPICAL CHARACTERISTIC CURVES




Fig.1 Typical Peak Clamping Voltage




Fig.2 Pulse Waveform




Fig.3 Typical Junction Capacitance


PEC4102AS ~ PEC4105AS Series

Product and Packing Information


Part No.	Package Type	Packing Type	Marking
PEC4102AS	SOD-123	3K pcs / 7" reel	5SH
PEC4103AS	SOD-123	3K pcs / 7" reel	6SH
PEC4105AS	SOD-123	3K pcs / 7" reel	7SH

Packaging Information & Mounting Pad Layout

SOD-123 Dimension — Unit: inch(mm)



SOD-123 Pad Layout — Unit: inch(mm)



Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.