
PJS6812

20V N-Channel Enhancement Mode MOSFET

Voltage	20 V	Current	3.7A



Features

- $R_{DS(ON)}$, V_{GS}@4.5V, I_D@3.7A<56mΩ
- $R_{DS(ON)}$, V_{GS}@2.5V, I_D@2.8A<69mΩ
- $R_{DS(ON)}$, V_{GS}@1.8V, I_D@1.5A<98mΩ
- Advanced Trench Process Technology
- Specially Designed for Switch Load, PWM Application, etc
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case: SOT-23 6L Package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0005 ounces, 0.014 grams
- Marking: SE2

Maximum Ratings and Thermal Characteristics (T_A=25°C unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNIT
Drain-Source Voltage		V_{DS}	20	V
Gate-Source Voltage		V_{GS}	±12	V
Continuous Drain Current		I_D	3.7	A
Pulsed Drain Current		I_{DM}	14.8	A
Power Dissipation	T_a=25°C	P_D	1.25	W
	Derate above 25°C		10	mW/°C
Operating Junction and Storage Temperature Range		T_J,T_{STG}	-55~150	°C
Typical Thermal Resistance - Junction to Ambient(Note 3)		$R_{\theta JA}$	100	°C/W

PJS6812

Electrical Characteristics (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V, I_D=250uA	20	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=250uA	0.4	0.67	1.2	V
Drain-Source On-State Resistance	$R_{DS(on)}$	V_{GS}=4.5V, I_D=3.7A	-	41	56	mΩ
		V_{GS}=2.5V, I_D=2.8A	-	51	69	
		V_{GS}=1.8V, I_D=1.5A	-	69	98	
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=20V, V_{GS}=0V	-	-0.01	1	uA
Gate-Source Leakage Current	I_{GSS}	V_{GS}=±12V, V_{DS}=0V	-	±10	±100	nA
Dynamic						
Total Gate Charge	Q_g	V_{DS}=10V, I_D=3.7A, V_{GS}=4.5V(Note 1,2)	-	4.57	-	nC
Gate-Source Charge	Q_{gs}		-	0.77	-	
Gate-Drain Charge	Q_{gd}		-	0.98	-	
Input Capacitance	Ciss	V_{DS}=10V, V_{GS}=0V, f=1.0MHZ	-	350	-	pF
Output Capacitance	Coss		-	40	-	
Reverse Transfer Capacitance	Crss		-	29.3	-	
Switching						
Turn-On Delay Time	$td_{(on)}$	V_{DD}=10V, I_D=3.7A, V_{GS}=4.5V, R_G=6Ω(Note 1,2)	-	3.4	-	ns
Turn-On Rise Time	tr		-	47	-	
Turn-Off Delay Time	$td_{(off)}$		-	18	-	
Turn-Off Fall Time	tf		-	10	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I_S	---	-	-	1.5	A
Diode Forward Voltage	V_{SD}	I_S=1.0A, V_{GS}=0V	-	0.75	1.2	V

NOTES :

1. Pulse width≤300us, Duty cycle≤2%.
2. Essentially independent of operating temperature typical characteristics.
3. $R_{\Theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins mounted on a 1 inch FR-4 with 2oz. square pad of copper.
4. The maximum current rating is package limited.

PJS6812

TYPICAL CHARACTERISTIC CURVES




Fig.1 On-Region Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction temperature




Fig.5 On-Resistance Variation with VGS.




Fig.6 Body Diode Characteristics

PJS6812

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Threshold Voltage Variation with Temperature





Fig.9 Capacitance vs. Drain-Source Voltage.

PJS6812

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
PJS6812	SOT-23 6L	3K pcs / 7” reel	SE2
PJS6812	SOT-23 6L	10K pcs / 13” reel	SE2

Mounting Pad Layout



PJS6812

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from PANJIT International Inc..
- PANJIT International Inc. reserves the rights to make changes of the content herein the document follow PCN procedure. Please refer to our website for the latest document.
- PANJIT International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- PANJIT International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. PANJIT International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed or authorized for equipment relating to human life, life-saving or life-sustaining applications, such as medical instruments, transportation equipment, aerospace machinery, or for other applications intended to cause personal injury. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify PANJIT International Inc. for any damages resulting from such improper use or sale. For additional terms and conditions regarding the use of PANJIT products, please refer to the Terms of Use available on the PANJIT website.
- Since PANJIT uses lot number as the tracking base, please provide the lot number for tracking when complaining.