

SBA220AH / SBA230AH / SBA240AH

EXTREME LOW VF SCHOTTKY RECTIFIER

Voltage

20-40 V

Current

2 A

Features

- Ultra low forward voltage drop, low power loss
- Fast switching speed
- Surface mount package
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard


Applications

- Low voltage rectification
- Reverse polarity protection
- Low power consumption applications

Mechanical Data

- Case: Molded plastic, SOD-123HE
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0006 ounces, 0.0184 grams

SOD-123HE



1 Cathode 2 Anode

Maximum Ratings (T_A = 25 °C unless otherwise noted)

PARAMETER	SYMBOL	SBA220AH	SBA230AH	SBA240AH	UNIT
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	V
Maximum rms voltage	V _{RMS}	14	21	28	V
Maximum dc blocking voltage	V _R	20	30	40	V
Maximum average forward rectified current	I _{F(AV)}	2			A
Peak forward surge current: 8.3ms single half sine-wave Superimposed on rated load	I _{FSM}	30			A
Typical thermal resistance	R _{θJC} ⁽¹⁾	20			°C/W
	R _{θJA} ⁽²⁾	185			
Operating junction temperature range	T _J	-55 to +150			°C
Storage temperature range	T _{STG}	-55 to +150			°C

Electrical Characteristics

PARAMETER	SYMBOL	TEST CONDITION	SBA220AH		SBA230AH		SBA240AH		UNIT
			TYP.	MAX.	TYP.	MAX.	TYP.	MAX.	
Forward voltage	V _F	I _F = 10mA	0.21	-	0.21	-	0.22	-	V
		I _F = 0.5A	0.33	-	0.34	-	0.37	-	
		I _F = 2A	-	0.46	-	0.49	-	0.53	
		I _F = 10mA	0.09	-	0.09	-	0.1	-	V
Reverse current	I _R ⁽³⁾	I _F = 0.5A	0.24	-	0.26	-	0.27	-	
		V _R = 10V	14	-	9	-	7.4	-	μA
		V _R = 20V	-	100	25	-	9.6	-	
		V _R = 30V	-	-	-	100	16	-	
		V _R = 40V	-	-	-	-	-	100	
		V _R = 20V	6.1	-	3.7	-	2.3	-	mA
		V _R = 30V	-	-	9.6	-	3.5	-	
		V _R = 40V	-	-	-	-	5.6	-	

Note : 1. Mounted on a FR4 PCB, single-sided copper, with 100cm² copper pad area.

2. Mounted on a FR4 PCB, single-sided copper, mini pad.

3. Short duration pulse test used to minimize self-heating effect.

SBA220AH / SBA230AH / SBA240AH

TYPICAL CHARACTERISTIC CURVES




Fig.1 Forward Current Derating Curve




Fig. 2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Reverse Characteristics




Fig.5 Typical Reverse Characteristics







Fig.6 Typical Forward Characteristics

SBA220AH / SBA230AH / SBA240AH





SBA220AH / SBA230AH / SBA240AH

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
SBA220AH_R1_00001	SOD-123HE	3K pcs / 7" reel	B7
SBA230AH_R1_00001	SOD-123HE	3K pcs / 7" reel	E7
SBA240AH_R1_00001	SOD-123HE	3K pcs / 7" reel	F7

Packaging Information & Mounting Pad Layout



SBA220AH / SBA230AH / SBA240AH

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.