

SBA320AH-AU / SBA330AH-AU / SBA340AH-AU

EXTREME LOW VF SCHOTTKY RECTIFIER

Voltage

20-40 V

Current

3 A

Features

- Ultra low forward voltage drop, low power loss
- Fast switching speed
- Surface mount package
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard
- AEC-Q101 qualified



Applications

- Low voltage rectification
- Reverse polarity protection
- Low power consumption applications

Mechanical Data

- Case: Molded plastic, SOD-123HE
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0006 ounces, 0.0184 grams

SOD-123HE



Maximum Ratings (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	SBA320AH-AU	SBA330AH-AU	SBA340AH-AU	UNIT
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	V
Maximum RMS voltage	V _{RMS}	14	21	28	V
Maximum DC blocking voltage	V _R	20	30	40	V
Maximum average forward rectified current	I _{F(AV)}	3			A
Peak forward surge current : 8.3ms single half sine-wave Superimposed on rated load	I _{FSM}	50			A
Typical thermal resistance	R _{θJC} ⁽²⁾	20			°C/W
	R _{θJA} ⁽¹⁾	185			
Operating junction temperature range	T _J	-55 to +150			°C
Storage temperature range	T _{STG}	-55 to +150			°C

Electrical Characteristics

PARAMETER	SYMBOL	TEST CONDITION		SBA320AH-AU		SBA330AH-AU		SBA340AH-AU		UNIT
				TYP.	MAX.	TYP.	MAX.	TYP.	MAX.	
Forward voltage	V _F	I _F = 10mA	T _J = 25 °C	0.19	-	0.19	-	0.21	-	V
		I _F = 1A		0.32	-	0.33	-	0.35	-	
		I _F = 3A		-	0.44	-	0.46	-	0.48	
		I _F = 10mA	T _J = 125 °C	0.05	-	0.06	-	0.06	-	V
		I _F = 1A		0.24	-	0.26	-	0.27	-	
Reverse current	I _R ⁽³⁾	V _R = 10V	T _J = 25 °C	31	-	18	-	16	-	μA
		V _R = 20V		-	200	28	-	21	-	
		V _R = 30V		-	-	-	200	35	-	
		V _R = 40V		-	-	-	-	-	150	
		V _R = 20V	T _J = 125 °C	8.6	-	5.6	-	5.1	-	mA
		V _R = 30V		-	-	10.7	-	7.6	-	
		V _R = 40V		-	-	-	-	12	-	
		V _R = 40V		-	-	-	-	-	-	

Note: 1. Mounted on a FR4 PCB, single-sided copper, mini pad.

2. Mounted on a FR4 PCB, single-sided copper, with 100cm² copper pad area.

3. Short duration pulse test used to minimize self-heating effect.

SBA320AH-AU / SBA330AH-AU / SBA340AH-AU

TYPICAL CHARACTERISTIC CURVES




Fig.1 Forward Current Derating Curve




Fig. 2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Reverse Characteristics




Fig.5 Typical Forward Characteristics




Fig.6 Typical Forward Characteristics

SBA320AH-AU / SBA330AH-AU / SBA340AH-AU




Fig.7 Typical Forward Characteristics




Fig.8 Typical Forward Characteristics






Fig.9 Operating Temperature Derating Curve

SBA320AH-AU / SBA330AH-AU / SBA340AH-AU

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
SBA320AH-AU	SOD-123HE	3K pcs / 7" reel	G7
SBA330AH-AU	SOD-123HE	3K pcs / 7" reel	H7
SBA340AH-AU	SOD-123HE	3K pcs / 7" reel	L7

Packaging Information & Mounting Pad Layout



SBA320AH-AU / SBA330AH-AU / SBA340AH-AU

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from PANJIT International Inc..
- PANJIT International Inc. reserves the rights to make changes of the content herein the document follow PCN procedure. Please refer to our website for the latest document.
- PANJIT International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- PANJIT International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. PANJIT International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed or authorized for equipment relating to human life, life-saving or life-sustaining applications, such as medical instruments and aerospace machinery, or for other applications intended to cause personal injury. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify PANJIT International Inc. for any damages resulting from such improper use or sale. For additional terms and conditions regarding the use of PANJIT products, please refer to the Terms of Use available on the PANJIT website.
- Since PANJIT uses lot number as the tracking base, please provide the lot number for tracking when complaining.