

PJA3428-AU

30V N-Channel Enhancement Mode MOSFET

Voltage

30 V

Current

300mA



Features

- Advanced Trench Process Technology
- ESD Protected
- Specially Designed for Relay driver, Speed line drive, etc
- AEC-Q101 qualified
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : SOT-23 Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.0084 grams

SOT-23



Maximum Ratings and Thermal Characteristics (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNITS	
Drain-Source Voltage	V _{DS}	30	V	
Gate-Source Voltage	V _{GS}	±10	V	
Continuous Drain Current ^(Note 4)	I _D	300	mA	
Pulsed Drain Current ^(Note 1)	I _{DM}	600	mA	
Power Dissipation	P _D	T _A =25°C	500	mW
		Derate above 25°C	4	mW/°C
Operating Junction and Storage Temperature Range	T _J , T _{STG}	-55~150	°C	
Typical Thermal Resistance	R _{θJA}	250	°C/W	
- Junction to Ambient ^(Note 3,4)				

PJA3428-AU

Electrical Characteristics (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250uA	30	-	-	V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250uA	0.4	0.75	1	V
Drain-Source On-State Resistance	R _{DS(on)}	V _{GS} =4.5V, I _D =300mA	-	0.7	1.2	Ω
		V _{GS} =2.5V, I _D =200mA	-	0.8	1.6	
		V _{GS} =1.8V, I _D =100mA	-	0.9	2	
		V _{GS} =1.5V, I _D =50mA	-	1.1	3	
		V _{GS} =1.2V, I _D =20mA	-	1.5	4	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =24V, V _{GS} =0V	-	-	1	uA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =±8V, V _{DS} =0V	-	-	±10	uA
Dynamic (Note 5)						
Total Gate Charge	Q _g	V _{DS} =10V, I _D =300mA, V _{GS} =4.5V	-	0.9	-	nC
Gate-Source Charge	Q _{gs}		-	0.3	-	
Gate-Drain Charge	Q _{gd}		-	0.2	-	
Input Capacitance	C _{iss}	V _{DS} =10V, V _{GS} =0V, f=1MHz	-	45	-	pF
Output Capacitance	C _{oss}		-	14	-	
Reverse Transfer Capacitance	C _{rss}		-	0.8	-	
Turn-On Delay Time	t _{d(on)}	V _{DD} =10V, I _D =300mA, V _{GS} =4V, R _G =10Ω ^(Note 1,2)	-	8.3	-	ns
Turn-On Rise Time	t _r		-	5.7	-	
Turn-Off Delay Time	t _{d(off)}		-	35	-	
Turn-Off Fall Time	t _f		-	12	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I _S	---	-	-	300	mA
Diode Forward Voltage	V _{SD}	I _S =300mA, V _{GS} =0V	-	0.9	1.3	V

NOTES :

1. Pulse width ≤ 300us, Duty cycle ≤ 2%.
2. Essentially independent of operating temperature typical characteristics.
3. R_{θJA} is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins mounted on a 1 inch FR-4 with 2oz. square pad of copper.
4. The maximum current rating is package limited.
5. Guaranteed by design, not subject to production testing.

PJA3428-AU

TYPICAL CHARACTERISTIC CURVES




Fig.1 On-Region Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction temperature




Fig.5 On-Resistance Variation with V_{GS} .




Fig.6 Body Diode Characteristics

PJA3428-AU

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Breakdown Voltage Variation vs. Temperature




Fig.9 Threshold Voltage Variation with Temperature.






Fig.10 Capacitance vs. Drain-Source Voltage.

PJA3428-AU

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
PJA3428-AU	SOT-23	3K pcs / 7" reel	A28

Packaging Information & Mounting Pad Layout



PJA3428-AU

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.