

Surface Mount Glass Passivated Bridge Rectifier

Voltage

1000 V

Current

6A

Features



- Glass passivated chip junction
- Ideally suited for automatic assembly
- Save space on printed circuit boards
- Ultra thin profile package for space constrained utilization
- Lead free in compliance with EU RoHS 2.0
- Halogen-free according to IEC 61249 standard


Mechanical Data

- Case : M6 Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.38 grams

Application

- PD Charger
- Consumer Power Adapter
- NB Adapter
- TV Power

M6



Key Parameters	
Parameter	Value
V_{RRM}	1000V
$I_F(AV)$	6A
I_{FSM}	150A
I_R	5uA
Package	M6

Maximum Ratings and Thermal Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNITS
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	1000	V
Maximum RMS Voltage		V_{RMS}	700	V
Maximum DC Blocking Voltage		V_{DC}	1000	V
Maximum Average Forward Current		$I_{F(AV)}$	6	A
Peak Forward Surge Current : 8.3 ms Single Half Sine-Wave Superimposed On Rated Load	@ $T_A = 25^\circ\text{C}$	I_{FSM}	150	A
	@ $T_A = 125^\circ\text{C}$		120	
Peak Forward Surge Current : 1.0 ms Single Half Sine-Wave Superimposed On Rated Load	@ $T_A = 25^\circ\text{C}$	I_{FSM}	300	A
	@ $T_A = 125^\circ\text{C}$		240	
$I^2 t$ rating for fusing ($t = 8.3\text{ms}$)		$I^2 t$	93.4	A^2S
Typical Junction Capacitance Measured at 1 MHz And Applied $V_R = 4\text{ V}$		C_J	50	pF
Typical Thermal Resistance (Note 1)		$R_{\theta JA}$	55	$^\circ\text{C/W}$
		$R_{\theta JL}$	10	
		$R_{\theta JC}$	6	
Operating junction and storage temperature range		T_J, T_{STG}	-55~150	$^\circ\text{C}$





Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Forward Voltage	V_F	$I_F = 3\text{ A}, T_J = 25^\circ\text{C}$	-	0.90	1.0	V
		$I_F = 3\text{ A}, T_J = 125^\circ\text{C}$	-	0.80	-	
Reverse Current	I_R	$V_R = 1000\text{ V}, T_J = 25^\circ\text{C}$	-	-	5	μA
		$V_R = 1000\text{ V}, T_J = 125^\circ\text{C}$	-	-	100	

NOTES :

1. Device mounted on P.C.B with 35mm*25mm*1.7mm.

TYPICAL CHARACTERISTIC CURVES



Product and Packing Information

Part No.	Package Type	Packing Type	Marking
PMSM610	M6	1.8K pcs / 13" reel	PMSM610

Packaging Information & Mounting Pad Layout


M6 Dimension

Unit: inch(mm)

Technical drawing of the M6 package showing three views: side, top, and bottom. The side view shows dimensions L (length), A1 (lead height), c (lead thickness), and r (fillet radius). The top view shows dimensions D (package width), m (package height), b (lead width), and e (pitch). The bottom view shows dimension A (lead thickness). Polarity markings (- and +) are shown on the top view.

M6 Dimension.Unit:Inch (mm)

Dim	Unit (Inch)		Unit (mm)	
	Min	Max	Min	Max
A	0.055	0.071	1.40	1.80
A1	-	0.006	-	0.15
b	0.051	0.059	1.30	1.50
c	0.008	0.012	0.20	0.30
D	0.394	0.409	10.00	10.40
E	0.268	0.283	6.80	7.20
E1	0.382	0.398	9.70	10.10
e	0.193	0.201	4.90	5.10
L	0.02	0.043	0.50	1.10

M6 Pad Layout	Unit: inch(mm)
 The diagram shows the mounting pad layout for the M6 package. It is a square array of four pads. The center-to-center distance between pads is 0.364 inches (9.25 mm). The pad width is 0.039 inches (1.00 mm). The pad thickness is 0.059 inches (1.50 mm). The distance from the center of the pad array to the edge of the package is 0.197 inches (5.00 mm).	

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document follow PCN procedure. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.