

PJD30P08A-AU

80V P-Channel Enhancement Mode MOSFET

Voltage

-80 V

Current

-19 A


Features

- $R_{DS(ON)}$, $V_{GS}@-10V$, $I_D@-15A < 83m\Omega$
- $R_{DS(ON)}$, $V_{GS}@-4.5V$, $I_D@-10A < 94m\Omega$
- 100% UIS tested
- Reliable and Rugged
- AEC-Q101 qualified
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : TO-252AA Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.3217 grams

TO-252AA



Maximum Ratings and Thermal Characteristics ($T_A=25^\circ C$ unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNIT
Drain-Source Voltage		V_{DS}	-80	V
Gate-Source Voltage		V_{GS}	± 20	
Continuous Drain Current ^(Note 3)	$T_C=25^\circ C$	I_D	-19	A
	$T_C=100^\circ C$		-13	
Pulsed Drain Current ^(Note 1)	$T_C=25^\circ C$	I_{DM}	-36	
Power Dissipation	$T_C=25^\circ C$	P_D	64	W
	$T_C=100^\circ C$		32	
Continuous Drain Current ^(Note 4)	$T_A=25^\circ C$	I_D	-4.1	A
	$T_A=70^\circ C$		-3.4	
Power Dissipation	$T_A=25^\circ C$	P_D	3	W
	$T_A=70^\circ C$		2.1	
Single Pulse Avalanche Current ^(Note 5)		I_{AS}	-10.5	A
Single Pulse Avalanche Energy ^(Note 5)		E_{AS}	55	mJ
Operating Junction and Storage Temperature Range		T_J, T_{STG}	-55~175	$^\circ C$
Thermal Resistance ^(Note 4)	Junction to Case	$R_{\theta JC}$	2.35	$^\circ C/W$
	Junction to Ambient	$R_{\theta JA}$	50	

PJD30P08A-AU

Electrical Characteristics (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Static						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =-250uA	-80	-	-	V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =-250uA	-1.2	-1.6	-2.5	
Drain-Source On-State Resistance	R _{DS(on)}	V _{GS} =-10V, I _D =-15A	-	66	83	mΩ
		V _{GS} =-4.5V, I _D =-10A	-	72	94	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-80V, V _{GS} =0V	-	-	-1	uA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V	-	-	±100	nA
Dynamic ^(Note 6)						
Total Gate Charge	Q _g	V _{DS} =-40V, I _D =-15A, V _{GS} =-10V	-	31	41	nC
Gate-Source Charge	Q _{gs}		-	6	-	
Gate-Drain Charge	Q _{gd}		-	5.2	-	
Input Capacitance	C _{iss}	V _{DS} =-40V, V _{GS} =0V, f=1MHz	-	1722	2300	pF
Output Capacitance	C _{oss}		-	72	144	
Reverse Transfer Capacitance	C _{rss}		-	53	106	
Gate resistance	R _g	f=1MHz	-	9.3	-	Ω
Turn-On Delay Time	td _(on)	V _{DS} =-40V, I _D =-15A, V _{GS} =-10V, R _G =3Ω (Note 2)	-	5.4	-	ns
Turn-On Rise Time	tr		-	5.7	-	
Turn-Off Delay Time	td _(off)		-	47	-	
Turn-Off Fall Time	tf		-	29	-	
Drain-Source Diode						
Diode Forward Current	I _S	T _C =25° C (Package Limit)	-	-	-19	A
Pulsed Diode Forward Current	I _{SM}		-	-	-36	
Diode Forward Voltage	V _{SD}	I _S =-20A, V _{GS} =0V	-	-0.9	-1.3	V
Reverse Recovery Time	T _{rr}	V _{DD} =-40V, V _{GS} =0V	-	16	-	ns
Reverse Recovery Charge	Q _{rr}	I _S =-15A, dI _S /dt=100A/us	-	14	-	nC

NOTES :

1. Pulse width ≤ 300us, Duty cycle ≤ 2%.
2. Essentially independent of operating temperature typical characteristics.
3. The maximum current rating is package limited.
4. R_{θJA} is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. Mounted on a 1 inch² with 2oz.square pad of copper.
5. E_{AS} is calculated based on the condition of L=1mH, I_{AS}=-10.5A, V_{DD}=-30V, V_{GS}=-10V. 100% test at L=0.5mH, I_{AS}=-11A in production.
6. Guaranteed by design, not subject to production testing.

PJD30P08A-AU

TYPICAL CHARACTERISTIC CURVES




Fig.1 On-Region Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction temperature




Fig.5 On-Resistance Variation with V_{GS}




Fig.6 Source-Drain Diode Forward Voltage

PJD30P08A-AU

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Breakdown Voltage Variation vs. Temperature




Fig.9 Threshold Voltage Variation with Temperature




Fig.10 Capacitance vs. Drain-Source Voltage




Fig.11 Maximum Safe Operating Area






Fig.12 Normalized Transient Thermal Impedance

PJD30P08A-AU

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
PJD30P08A-AU	TO-252AA	3K pcs / 13" reel	D30P08A

Packaging Information & Mounting Pad Layout



PJD30P08A-AU

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from PANJIT International Inc..
- PANJIT International Inc. reserves the rights to make changes of the content herein the document follow PCN procedure. Please refer to our website for the latest document.
- PANJIT International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- PANJIT International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. PANJIT International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed or authorized for equipment relating to human life, life-saving or life-sustaining applications, such as medical instruments, transportation equipment, aerospace machinery, or for other applications intended to cause personal injury. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify PANJIT International Inc. for any damages resulting from such improper use or sale. For additional terms and conditions regarding the use of PANJIT products, please refer to the Terms of Use available on the PANJIT website.
- Since PANJIT uses lot number as the tracking base, please provide the lot number for tracking when complaining.