Glass Passivated Bridge Rectifier

Voltage	1000 V	Current	25A

KBJ-2

Features

- Glass passivated chip junction
- UL recognition file number E526209
- Lead free in compliance with EU RoHS 2.0
- Halogen-free according to IEC 61249 standard

Mechanical Data

- Case : KBJ-2 Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 4.1442 grams



Application

- Computing Power / Desktop Power
- Game Console Power
- Server Power
- Air Conditioner out door power board
- High Power/High Efficiency Power
- Home Appliances Power Board

Key Parameters	
Parameter	**Value**
V_{RRM}	1000V
$I_{F}(AV)$	25A
I_{FSM}	240A
I_{R}	5uA
Package	KBJ-2

Maximum Ratings and Thermal Characteristics (T_A = 25 °C unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNITS
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	1000	V
Maximum RMS Voltage		V_{RMS}	700	V
Maximum DC Blocking Voltage		V_{DC}	1000	V
Maximum Average Forward Current	With heatsink	$I_{F(AV)}$	25	A
	Without heatsink		2.6	
Peak Forward Surge Current : 8.3 ms Single Half Sine-Wave Superimposed On Rated Load	@ T_A = 25 °C	I_{FSM}	240	A
	@ T_A = 125 °C		192	
Peak Forward Surge Current : 1.0 ms Single Half Sine-Wave Superimposed On Rated Load	@ T_A = 25 °C	I_{FSM}	480	A
	@ T_A = 125 °C		384	
I^2t rating for fusing (t = 8.3ms)		I^2t	239	A^2S
Typical Junction Capacitance Measured at 1 MHZ And Applied V_R = 4 V		C_J	90	pF
Typical Thermal Resistance (Note 1) (with heatsink)		$R_{\theta JA}$	10	°C/W
		$R_{\theta JL}$	3	
		$R_{\theta JC}$	4	
Operating junction and storage temperature range		T_J, T_{STG}	-55~150	°C
Mounting torque @ Recommend torque:5Kg.cm		Tor	8	Kg.cm

Electrical Characteristics (T_A = 25 °C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Forward Voltage	V_F	I_F = 12.5 A, T_J = 25 °C	-	-	1.05	V
Reverse Current	I_R	V_R = 1000 V, T_J = 25 °C	-	-	5	uA
		V_R = 1000 V, T_J = 125 °C	-	-	100	

NOTES :

1. Device mounted on 10 cm * 9.4 cm * 2.6 cm Fin type heat sink .

TYPICAL CHARACTERISTIC CURVES



Fig.1 Forward Current Derating Curve



Fig.2 Typical Junction Capacitance



Fig.3 Typical Reverse Characteristics



Fig.4 Typical Forward Characteristics

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
KBJ2510	KBJ-2	20 pcs / tube	KBJ2510

Packaging Information

KBJ-2 Dimension — Unit: inch(mm)



KBJ-2 Dimension.Unit:Inch (mm)				
Dim	Unit (Inch)		Unit (mm)	
	Min	Max	Min	Max
A	0.972	0.996	24.70	25.30
B	0.579	0.602	14.70	15.30
C	0.669	0.709	17.00	18.00
D	0.287	0.303	7.30	7.70
E	0.366	0.382	9.30	9.70
F	0.130	0.146	3.30	3.70
G	0.059	0.075	1.50	1.90
H	0.035	0.043	0.90	1.10
I	0.173	0.189	4.40	4.80
J	Ø0.122	Ø0.142	Ø3.10	Ø3.60
K	0.098	0.114	2.50	2.90
L	0.014	0.031	0.55	0.80
M	0.041	0.057	1.05	1.45
N	0.067	0.083	1.70	2.10
P	0.134	0.150	3.40	3.80
Q	0.154	0.161	3.90	4.10
R	C0.118		3.00	

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.