

PE4305CS ~ PE4336CS Series

ESD Protection

Voltage

5~36 V


Features

- IEC61000-4-2 : $\pm 30\text{kV}$ Air, $\pm 30\text{kV}$ Contact
- IEC61000-4-5(Lightning) : 3.3~17.5A(8/20 μ S)
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : SOD-323 Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.0041 grams

SOD-323



Maximum Ratings and Thermal Characteristics (T_A = 25 °C unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNITS
ESD IEC61000-4-2(Air)	V _{ESD}	± 30	kV
ESD IEC61000-4-2(Contact)		± 30	
Typical Thermal Resistance ^(Note 1)	R _{θJA}	650	°C/W
Operating Junction Temperature Range	T _J	-55~150	°C
Storage Temperature Range	T _{STG}	-55~150	°C

PE4305CS ~ PE4336CS Series

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PE4305CS						
PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V_{RWM}	-	-	-	5	V
Reverse Breakdown Voltage	V_{BR}	$I_{BT} = 1\text{mA}$	6	-	8.5	V
Reverse Leakage Current	I_R	$V_R = 5\text{V}$	-	-	1	μA
Clamping Voltage	V_{CL}	$I_{PP} = 1\text{A}, t_P = 8/20\mu\text{s}$	-	-	8.5	V
		$I_{PP} = 17.5\text{A}, t_P = 8/20\mu\text{s}$	-	-	12.4	V
Off State Junction Capacitance	C_J	0Vdc Bias $f = 1\text{MHz}$	-	-	200	pF

PE4307CS						
PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V_{RWM}	-	-	-	7	V
Reverse Breakdown Voltage	V_{BR}	$I_{BT} = 1\text{mA}$	7.7	-	10	V
Reverse Leakage Current	I_R	$V_R = 7\text{V}$	-	-	1	μA
Clamping Voltage	V_{CL}	$I_{PP} = 1\text{A}, t_P = 8/20\mu\text{s}$	-	-	12	V
		$I_{PP} = 12.9\text{A}, t_P = 8/20\mu\text{s}$	-	-	16.8	V
Off State Junction Capacitance	C_J	0Vdc Bias $f = 1\text{MHz}$	-	-	160	pF

PE4309CS						
PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V_{RWM}	-	-	-	9	V
Reverse Breakdown Voltage	V_{BR}	$I_{BT} = 1\text{mA}$	9.9	-	12	V
Reverse Leakage Current	I_R	$V_R = 9\text{V}$	-	-	1	μA
Clamping Voltage	V_{CL}	$I_{PP} = 1\text{A}, t_P = 8/20\mu\text{s}$	-	-	13	V
		$I_{PP} = 9.5\text{A}, t_P = 8/20\mu\text{s}$	-	-	23	V
Off State Junction Capacitance	C_J	0Vdc Bias $f = 1\text{MHz}$	-	-	120	pF

PE4305CS ~ PE4336CS Series

PE4312CS

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V_{RWM}	-	-	-	12	V
Reverse Breakdown Voltage	V_{BR}	$I_{BT} = 1mA$	13.2	-	15.5	V
Reverse Leakage Current	I_R	$V_R = 12V$	-	-	1	μA
Clamping Voltage	V_{CL}	$I_{PP} = 1A, t_P = 8/20\mu s$	-	-	17	V
		$I_{PP} = 8.3A, t_P = 8/20\mu s$	-	-	26.5	V
Off State Junction Capacitance	C_J	0Vdc Bias $f = 1MHz$	-	-	90	pF

PE4315CS

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V_{RWM}	-	-	-	15	V
Reverse Breakdown Voltage	V_{BR}	$I_{BT} = 1mA$	16.5	-	20	V
Reverse Leakage Current	I_R	$V_R = 15V$	-	-	1	μA
Clamping Voltage	V_{CL}	$I_{PP} = 1A, t_P = 8/20\mu s$	-	-	22	V
		$I_{PP} = 7.8A, t_P = 8/20\mu s$	-	-	28	V
Off State Junction Capacitance	C_J	0Vdc Bias $f = 1MHz$	-	-	65	pF

PE4320CS

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V_{RWM}	-	-	-	20	V
Reverse Breakdown Voltage	V_{BR}	$I_{BT} = 1mA$	22	-	26	V
Reverse Leakage Current	I_R	$V_R = 20V$	-	-	1	μA
Clamping Voltage	V_{CL}	$I_{PP} = 1A, t_P = 8/20\mu s$	-	-	29	V
		$I_{PP} = 5.8A, t_P = 8/20\mu s$	-	-	38	V
Off State Junction Capacitance	C_J	0Vdc Bias $f = 1MHz$	-	-	55	pF

PE4305CS ~ PE4336CS Series

PE4324CS						
PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V_{RWM}	-	-	-	24	V
Reverse Breakdown Voltage	V_{BR}	$I_{BT} = 1mA$	26.4	-	31	V
Reverse Leakage Current	I_R	$V_R = 24V$	-	-	0.05	μA
Clamping Voltage	V_{CL}	$I_{PP} = 1A, t_P = 8/20\mu s$	-	-	35	V
		$I_{PP} = 4.8A, t_P = 8/20\mu s$	-	-	45	V
Off State Junction Capacitance	C_J	0Vdc Bias $f = 1MHz$	-	-	42	pF

PE4336CS						
PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V_{RWM}	-	-	-	36	V
Reverse Breakdown Voltage	V_{BR}	$I_{BT} = 1mA$	39.6	-	47	V
Reverse Leakage Current	I_R	$V_R = 36V$	-	-	0.05	μA
Clamping Voltage	V_{CL}	$I_{PP} = 1A, t_P = 8/20\mu s$	-	-	51	V
		$I_{PP} = 3.3A, t_P = 8/20\mu s$	-	-	65	V
Off State Junction Capacitance	C_J	0Vdc Bias $f = 1MHz$	-	-	20	pF

NOTES :

1. Mounted on a FR4 PCB, single-sided copper, standard footprint.
2. A transient suppressor is selected according to the working peak reverse voltage(V_{RWM}), which should be equal to or greater than the DC or continuous peak operation voltage level.

PE4305CS ~ PE4336CS Series

TYPICAL CHARACTERISTIC CURVES




Fig.1 Typical Peak Clamping Voltage




Fig.2 Pulse Waveform




Fig.3 Typical Junction Capacitance






Fig.4 TLP Measurement

PE4305CS ~ PE4336CS Series

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
PE4305CS	SOD-323	5K pcs / 7" reel	ACG
PE4307CS	SOD-323	5K pcs / 7" reel	ACJ
PE4309CS	SOD-323	5K pcs / 7" reel	ACK
PE4312CS	SOD-323	5K pcs / 7" reel	ACL
PE4315CS	SOD-323	5K pcs / 7" reel	ACM
PE4320CS	SOD-323	5K pcs / 7" reel	ACN
PE4324CS	SOD-323	5K pcs / 7" reel	ACP
PE4336CS	SOD-323	5K pcs / 7" reel	ACR

Packaging Information & Mounting Pad Layout



PE4305CS ~ PE4336CS Series

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document follow PCN procedure. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.