

115V N-Channel Enhancement Mode MOSFET

Voltage	115 V	R _{DSON}	7.6 mΩ
Current	91.4 A	Q _G (TYP)	77 nC

Feature

- R_{DSON}, V_{GS}@10V, I_D@20A<7.6mΩ
- R_{DSON}, V_{GS}@4.5V, I_D@10A<11mΩ
- High switching speed
- Low reverse transfer capacitance
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case: DFN5060-8L Package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0028 ounces, 0.08 grams

Application

- SR solutions of Travel Adapter, PD Charger, Gaming Adapter.

Absolute Maximum Ratings (T_A = 25 °C unless otherwise specified)

PARAMETER	SYMBOL	LIMIT	UNITS
Drain-Source Voltage	V _{DS}	115	V
Gate-Source Voltage	V _{GS}	+20/ -12	
Continuous Drain Current	T _C =25°C	91.4	A
	T _C =100°C	57.8	
Pulsed Drain Current (Note 1)	I _{DM}	365	A
Single Pulse Avalanche Current (Note 5)	I _{AS}	37	A
Single Pulse Avalanche Energy (Note 5)	E _{AS}	68	mJ
Power Dissipation	T _C =25°C	125	W
	T _C =100°C	50	
Operating Junction and & Storage Temperature Range	T _J , T _{STG}	-55~150	°C

Thermal Characteristics

PARAMETER	SYMBOL	TYPICAL	MAXIMUM	UNITS
Thermal Resistance (Note 4)	R _{θJC}	0.9	1	°C/W
	R _{θJT}	19.3	23	°C/W
	R _{θJA}	41	50	°C/W

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_D=250\mu\text{A}$	115	-	-	V
Gate Threshold Voltage	$\text{V}_{\text{GS}(\text{th})}$	$\text{V}_{\text{DS}}=\text{V}_{\text{GS}}, \text{I}_D=250\mu\text{A}$	1.2	1.7	2.5	
Drain-Source On-State Resistance	$\text{R}_{\text{DS}(\text{on})}$	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_D=20\text{A}$	-	6.1	7.6	$\text{m}\Omega$
		$\text{V}_{\text{GS}}=4.5\text{V}, \text{I}_D=10\text{A}$	-	8.4	11	
Zero Gate Voltage Drain Current	I_{DSS}	$\text{V}_{\text{DS}}=115\text{V}, \text{V}_{\text{GS}}=0\text{V}$	-	-	100	μA
Gate-Source Leakage Current	I_{GSS}	$\text{V}_{\text{GS}}=+20\text{V}, \text{V}_{\text{DS}}=0\text{V}$	-	-	100	nA
Dynamic (Note 6)						
Total Gate Charge	Q_g	$\text{V}_{\text{DS}}=60\text{V}, \text{I}_D=50\text{A}, \text{V}_{\text{GS}}=10\text{V}$	-	77	105	nC
Gate-Source Charge	Q_{gs}		-	15.9	-	
Gate-Drain Charge	Q_{gd}		-	16.9	-	
Plateau Voltage	V_{GP}		-	3.5	-	V
Input Capacitance	C_{iss}	$\text{V}_{\text{DS}}=60\text{V}, \text{V}_{\text{GS}}=0\text{V}, \text{f}=1.0\text{MHz}$	-	4740	-	pF
Output Capacitance	C_{oss}		-	338	-	
Reverse Transfer Capacitance	Crss		-	36	-	
Turn-On Delay Time	$\text{td}(\text{on})$	$\text{V}_{\text{DD}}=60\text{V}, \text{I}_D=50\text{A}, \text{V}_{\text{GS}}=10\text{V}, \text{R}_G=6\Omega$ (Note 2)	-	34	-	ns
Turn-On Rise Time	t_r		-	111	-	
Turn-Off Delay Time	$\text{td}(\text{off})$		-	116	-	
Turn-Off Fall Time	t_f		-	119	-	
Gate Resistance	R_g	$\text{f}=1.0\text{MHz}$	-	1.6	-	Ω
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I_s	$\text{T}_c = 25^\circ\text{C}$	-	-	107	A
Diode Forward Voltage	V_{SD}	$\text{I}_s=1\text{A}, \text{V}_{\text{GS}}=0\text{V}$	-	0.68	1	V
Reverse Recovery Time	Tr_r	$\text{V}_r = 100\text{V}, \text{I}_s = 10\text{A}$ $\text{di}/\text{dt} = 100\text{A}/\text{us}$, $\text{T}_j = 25^\circ\text{C}$	-	62.7	-	ns
Reverse Recovery Charge	Q_{rr}		-	98	-	nC

NOTES :

1. Pulse width $\leq 300\text{us}$, Duty cycle $\leq 2\%$
2. Essentially independent of operating temperature typical characteristics.
3. The maximum current rating is package limited.
4. R_{\thetaJA} is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. Mounted on a 1 inch² with 2oz.square pad of copper.
5. The test condition is $L=0.1\text{mH}, \text{I}_{AS}=37\text{A}, \text{V}_{DD}=70\text{V}, \text{V}_{GS}=10\text{V}, \text{R}_G=25\text{ohm}$, Starting $\text{T}_J=25^\circ\text{C}$
6. Guaranteed by design, not subject to production testing.

TYPICAL CHARACTERISTIC CURVES




Fig.1 Output Characteristics

Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current

Fig.4 On-Resistance vs. Junction temperature




Fig.5 Capacitance vs. Drain-Source Voltage

Fig.6 Source-Drain Diode Forward Voltage

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Breakdown Voltage Variation vs. Temperature




Fig.9 Threshold Voltage Variation with Temperature




Fig.10 Maximum Safe Operating Area




Fig.11 Maximum Safe Operating Area





Fig.12 Normalized Transient Thermal Impedance

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
PSMQC076N12LS1	DFN5060-8L	3000pcs / 13" reel	076N12LS

Packaging Information & Mounting Pad Layout



Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.